


## WS-2000(2)

### SPECIFICATIONS

- Suitable for FCC,FIZ
- Confidency by metal case
- Excellent Filtering
- Low leakage
- Confidency by Epoxy Coverage
- Best characteristic in high voltage
-  Approved



### APPLICATIONS

- AVR,UPS,INVERTER,CONVERTER ETC
- FACTORY AUTOMATION PRODUCT LINE
- MOTOR-DRIVEN Equipments
- OA Equipments
- Measuring Equipments
- Numerical Control Equipments

### SPECIFICATIONS

| MODEL                 | WS - 2030  | WS - 2040 | WS - 2050 | WS - 2060 |
|-----------------------|--|-----------|-----------|-----------|
| RATED CURRENT         | 30A  | 40A       | 50A       | 60A       |
| RATED VOLTAGE         | 250 VAC  |           |           |           |
| TEST VOLTAGE          | 2,500V 10mA between I/O terminals and Earth for 1 minute |           |           |           |
| INSULATION VOLTAGE    | 500VDC 300Mohm between I/O terminals and case            |           |           |           |
| LEAKAGE CURRENT       | 1mA Max  |           |           |           |
| TEMPERATURE RISE      | 30°C Max   |           |           |           |
| OPERATING TEMPERATURE | -25 ~ +85°C  |           |           |           |

### Block Diagram

