

**WS-2□□□(3)**

**SPECIFICATIONS**

- Suitable for FCC,FIZ
- Confidency by metal case
- Excellent Filtering
- Low leakage
- Confidency by Epoxy Coverage
- Best characteristic in high voltage
- **CE TUV Approved**



**APPLICATIONS**

- AVR,UPS,INVERTER,CONVERTER ETC
- FACTORY AUTOMATION PRODUCT LINE
- MOTOR-DRIVEN Equipments
- OA Equipments
- Measuring Equipments
- Numerical Control Equipments

**SPECIFICATIONS**

| MODEL                 | WS - 2080  | WS - 2100 | WS - 2120 | WS - 2150 |
|-----------------------|--|-----------|-----------|-----------|
| RATED CURRENT         | 80A  | 100A      | 120A      | 150A      |
| RATED VOLTAGE         | 250 VAC  |           |           |           |
| TEST VOLTAGE          | 2,500V 10mA between I/O terminals and Earth for 1 minute |           |           |           |
| INSULATION VOLTAGE    | 500VDC 300Mohm between I/O terminals and case            |           |           |           |
| LEAKAGE CURRENT       | 1mA Max  |           |           |           |
| TEMPERATURE RISE      | 30°C Max   |           |           |           |
| OPERATING TEMPERATURE | -25 ~ +85°C  |           |           |           |

**Block Diagram**

