



M.I.E SLOTTED TRUNKING



ISO9001, ROHS, UL94V-0 CERTIFIED



MODEL	W x H (mm)	SLOT WIDTH (Q) (mm)	FINGER WIDTH (P) (mm)	QTY / CARTON
MIE-ST-2525-4	25 X 25	4	6	50
MIE-ST-2545-4	25 X 45	4	6	50
MIE-ST-2565-4	25 X 65	4	6	50
MIE-ST-3345-4	33 X 45	4	6	50
MIE-ST-3365-4	33 X 65	4	6	50
MIE-ST-4060-4	40 X 60	4	6	50
MIE-ST-4080-4	40 X 80	4	6	30
MIE-ST-4565-4	45 X 65	4	6	50
MIE-ST-6565-4	65 X 65	4	6	30
MIE-ST-2545-6	25 X 45	6	8	50
MIE-ST-2565-8	25 X 65	8	10	50
MIE-ST-3365-8	33 X 65	8	10	50
MIE-ST-4565-8	45 X 65	8	10	50
MIE-ST-4080-8	40 X 80	8	6	30
MIE-ST-6080-8	60 X 80	8	10	30
MIE-ST-8080-8	80 X 80	8	10	24
MIE-ST-50100-10	50 X 100	10	13	30
MIE-ST-80100-10	80 X 100	10	13	18
MIE-ST-100100-10	100 X 100	10	13	18

Specifications

Material: Environmentally friendly and durable PVC, excellent insulation performance and is noncombustible. It holds RoHS certification, ensuring its environmental friendliness and no harmful elements such as lead.

Fire Resistance: UL94V-0 approved, flame-retardant properties with effective self-extinguishing capabilities and reliable insulation.

Operating Temperature: Temperature resistance from -20°C to 70°C during operation and capable of withstanding resting temperatures as low as -40°C, it can endure short-term exposure of up to 85°C.

Features

The duct and cover feature a reverse-buckle design, ensuring they never slide off. The smooth surface facilitates convenient and quick installation while effectively preventing unintended dislodgment due to vibrations.

The slot is smooth and free of glitches, ensuring a safe environment that won't cause cuts or abrasions to hands and wires.

With low-thread holes, the product allows for easy combination, disassembly, and wiring, providing a hassle-free user experience.